

HEBESCHIEBE

- Uygulama alanında en az 20 cm duvar kalınlığına ihtiyaç vardır.
- Bir kanat için taşıma kapasitesi 300 kg olup, yatay 3000 mm, dikey 2765 mm ye kadar kanat yapılabilir.
- Özel tasarlanmış taşıyıcı araba sayesinde son derece sessiz ve kolay çalışır ve istenilen noktada kanat sabitlenebilir.
- 4 kanatlı bir sistemde 12000 mm kadar genişlikteki alanlarda uygulanabilir.
- At least 20 cm wall thickness is needed in the application area.
- For a sash, the carrying capacity is 300 kg and it can be made up to 3000 mm horizontal and up to 2765 mm vertical.
- It is very quiet and easy to operate thanks to the specially designed carriage and the wing can be fixed at the desired point.
- It can be applied in areas with a width of 12000 mm in a system with 4 blades.

Daha Geniş, Daha Ferah Manzara İsteyenlere
For Those Who Want a Wider, More Spacious View



24, 32, 42 mm cam kalınlıkları

24, 32, 42 mm glass thickness



Estetik görümlü çift cam çıtası

Aesthetic appearance with double glazing bead




Isı, ses, toz ve suyu absorbe eden özel conta

Special gasket absorbing heat, noise, dust and water



Destek sacı
Reinforcement steel



185mm KASA FRAME

80mm KANAT SASH



SİSTEM PROFİLLERİ

SYSTEM PROFILES

HEBESCHIEBE

